



WFA2610

DC~26.5GHz, 10W

Features:

- * Low VSWR
- * High Attenuation Flatness

Applications:

- * Wireless
- * Transmitter
- * Laboratory Test
- * Radar

Electrical

Frequency: DC~26.5GHz
 Attenuation: 1~70dB
 Impedance: 50Ω
 Average Power*1: 10W@25°C max.
 Peak Power: 500W (5μS pulse width, 1% duty cycle) @SMA
 1KW (5μS pulse width, 0.5% duty cycle) @3.5mm

[1] Derated linearly to [0.5W@120°C.@SMA](#)
 [2] Derated linearly to 1W@125°C.@3.5mm



Mechanical

RF Connectors: SMA, 3.5mm
 Housing: Aluminum
 Outer Conductor: Passivated stainless steel or gold/nickel plated brass
 Male Inner Conductor: Gold plated brass
 Female Inner Conductor: Gold plated beryllium copper

Environmental

Temperature: -55~+85°C

Outline Drawings



Unit: mm [in]
 Tolerance: ±2mm [±0.08in]

Attenuation Accuracy and VSWR (SMA)

Frequency (GHz)	Attenuation Accuracy (±dB) vs. Attenuation (dB)				VSWR (max.)
	1~10	11~20	21~30	31~40	
DC~4	±0.7	±0.7	±0.7	±0.7	1.15
DC~8	±0.7	±0.7	±0.7	±0.8	1.2
DC~12.4	±0.8	±0.8	±0.9	±0.9	1.25
DC~18	±1	±1	±1	±1.2	1.3
DC~26.5	±1	±1.1	±1.2	±1.3	1.35

Attenuation Accuracy and VSWR (3.5mm)

Frequency (GHz)	Attenuation Accuracy (±dB) vs. Attenuation (dB)						VSWR (max.)
	1~10	20, 30	40	50	60	70	
DC~12.4	±0.6	±0.5	-0.5/+0.7	±1	-1/+1.5	-1.2/+1.5	1.15
DC~18	±0.8	±0.8	-0.5/+1	-1/+1.2	-1/+1.5	-1.2/+1.5	1.2
DC~26.5	±1	-0.5/+1.2	-0.5/+1.2	-1/+1.5	-1/+1.5	-1.2/+1.8	1.25



HowTo Order

WFA2610-X-Y-Z

X: Frequency in GHz

Y: Attenuation in dB

Z: Connector type

Connector naming rules:

S -SMA (Outline A)

3 - 3.5mm (Outline B)

Examples:

To order an attenuator,

DC-26.5GHz, SMA male to SMA female, 20dB attenuation,

specify WFA2610-26.5-20-S.

